





Silent Micro Power Pack

Your Comfort above all

Noise reduction up to -10 dBA

Operating frequency ranges adapted

Wide range of pressure From 125 to 250 bar

CAPACITIES	1	1,25	1,5	1,7	2	CC/REV
OPERATING PRESSURE	250	200	175	150	125	BAR



Silent

Noise reduction is the real challenge for today's industrial market





Unique 22-tooth helical pinion set

JTEKT HPI answers to your requirements

UNIQUE PROFILE OF SIDE PLATE

- From steering system technology in Automotive industry
- New tests and R&D Department researches launched to cover a wider range of capacities and pressures

NEW DESIGN HELICAL PROFILE


- 22-tooth helical profile for series 0 pumps: unique for that size of pump
- With suitable propeller angle
- Reduces significantly the hydraulic pulsations

OPERATING FREQUENCY RANGES ADAPTED

• More pleasant working conditions for the user



- Structure-borne sound: the pump hydraulic pulsations, being propagated through hoses and pipes, and then affecting the truck structure via the frame.
- Aerial noise: rotation frequency of an electric motor or a pump, which can be contained by an acoustic cover.



Tests realized in our own anechoic room on power pack with a 1.2Kw motor

CONTACT

ZI- 26 rue Condorcet - BP 87 94432 Chennevières-sur-Marne FRANCE Tel. +33 (0)1 49 62 28 00 Fax +33 (0)1 45 76 68 40 marketing@jtekt-hpi.com



